



Star Shape Molded Grip

- Use with hot or cold water
- Linear aeration provides continuous air flow between hand and exclusive Suttner "star-shaped" grip
- Grip directly molded on to lance providing protection and strength



- 1/4" pipe
- 10.5 GPM maximum
- 6000 PSI maximum
- 300°F maximum

Part	Size
5853	12" ST007 zinc plate
1713	24" ST007 zinc plate
1714	36" ST007 zinc plate
1716	48" ST007 zinc plate
1717	59" ST007 zinc plate
1718	79" ST007 zinc plate
6821	36" ST002 stainless
6822	48" ST002 stainless

Vented Grip

Vented grip allows heat to dissipate providing a cooler handle. Easily adjusts anywhere on lance for ergonomic positioning.



- Zinc plated steel
- 300°F maximum
- 6000 PSI maximum
- 1/4" MPT inlet & outlet

Part	Size
3570	24"
2162	36"
2163	48"



Vented Grip

Vented grip allows air to pass over the pipe to dissipate heat



- 10.5 GPM maximum
- 300°F. Maximum
- 4100 PSI maximum
- 1/4" pipe

Part	Size
6767	18" Zinc Plate Steel
6768	24" Zinc Plate Steel
6769	36" Zinc Plate Steel
6770	48" Zinc Plate Steel
6771	59" Zinc Plate Steel
6772	79" Zinc Plate Steel
6773	24" Stainless Steel
6774	36" Stainless Steel
6775	48" Stainless Steel
6776	59" Stainless Steel
6777	79" Stainless Steel



Non Insulated Pipes

•1/4" MPT

Part	Size
1520	12" Plated Steel
4698	18" Plated Steel
3378	24" Plated Steel
1745	36" Plated Steel
2158	48" Plated Steel
2159	59" Plated Steel
2160	79" Plated Steel
4513	24" Stainless Steel
2277	36" Stainless Steel
4514	48" Stainless Steel
3248	59" Stainless Steel
2345	79" Stainless Steel
6462	24" Aluminum
6463	36" Aluminum
6464	48" Aluminum
6465	59" Aluminum
6372	79" Aluminum

Lance Side Handle

Slide over 1/4" non-insulated wand pipe or screw into a vented grip, or use C-clamp style to slide over and tighten onto lance



C-clamp

Part	Product
1536	Slide over
4886	C-clamp

Lance Grips

Molded grip can be used with 1/4" non insulated wand pipe to make molded grip lances, Screws included
 Make your own vented grip lances!



Part	Product
2276	Molded Grip 11.75" long
2167	Vented Grip 15" long

Deluxified dual lances equipped with a quick connect socket on high pressure outlet and soap nozzle on low pressure outlet

Dual Lances



- 10.5 GPM max
- 1/4" zinc plated steel pipe
- 300°F maximum
- 4100 PSI maximum



Part	Product
6557	40" MTM Dual lance
6558	MTM Deluxified lance

Deluxified dual lances equipped with a quick connect socket on high pressure outlet and soap nozzle on low pressure outlet

SUTTNER Dual Lances

For use when high and low pressures are needed, i.e., spray cleaning agents with low pressure through an injector valve and then cleaning with high pressure.

- 38" long
- 65° #30 Brass soap nozzle
- 10.5 GPM maximum
- 300°F maximum
- 1/4" MPT inlet
- 1/4" FPT outlets

ST-54 protective lip on side handle. Stainless steel internal adjustment rod for longer life. Protective valve cover for added safety



Part	Product
1699	ST-54
4392	ST-54 Deluxe
2326	ST-53
4503	ST-53 Deluxe
3469	ST-54 Repair kit
4243	ST-53 Valve Assembly
5892	ST53 Complete Valve

G Heavy Duty Dual Lances

- 1/8" zinc plated steel pipe
- 1/4" nozzle holders
- 3000 PSI maximum
- 10.5 GPM maximum
- 284° F. Maximum



Part	Product
1696	36" Dual lance
4193	36" Deluxified dual lance
1697	72" Dual lance
4393	72" Deluxified dual lance
3112	O-ring & seat repair kit
4331	10007270 Brass Nipple
3117	10007366 shutter
5829	Rubber handle

Hydro Stainless Steel Dual Lances

- 10.5 GPM maximum
- 4000 PSI maximum
- 302°F, maximum
- Nozzle protectors standard
- 1/4" stainless steel tubes



Part	Product
3476	40" MTM Dual lance
4502	MTM Deluxified lance
4582	Valve repair kit

mecline Dual Lances

Plastic cover over valve and enlarged nozzle protector for maximum operator comfort and safety

- 10.5 GPM maximum
- 3650 PSI maximum
- 302°F, maximum
- Nozzle protectors standard
- 1/4" stainless steel tubes
- Stainless steel seat



Part	Product
6846	40" AL345
6847	AL345 Deluxified
4840	Valve & handle repair kit

SUTTNER ST-85 Push & Pull lance

For hard to reach applications such as gutters, underneath fender walls, heavy equipment



- Angles from 20° to 90°
- Each desired angle remains stationary until adjusted
- 34" long stainless steel
- 3050 PSI maximum
- 300°F maximum
- 1/4" FPT I/O

Part	Product
6823	ST-85



Dual Lance w/Trigger

Switch from high to low pressure with a pull of the trigger

- Zinc plated steel pipes
- 3600 PSI maximum



Part	Product
3707	40" Lance w/trigger

HPC Bendable Wands

Ideal for washing vehicle wheel areas in car wash.

- 2250 PSI maximum
- 10 GPM maximum
- 195°F. Maximum
- 1/4" MPT inlet & outlet

Part	Product
4411	18" Black
6793	18" Blue
3342	24" Black





Telescopic Super Wands

The Giraffe extension wands operate with minimal pressure loss. This means that they may be used with downstream chemical injectors.

- 10.5 GPM maximum flow
- 4000 PSI maximum pressure
- 195°F. Maximum temperature
- 1/4" ID high pressure hose



Part	Product
6364	6'-18' Giraffe
6365	6'-24' Giraffe

Giraffe Replacement Parts

Part	Product
6344	DG4000TS18 complete spray gun 18'
6361	DG4000TS24 complete spray gun 24"
6345	2100001 spray gun repair kit
6348	680129 1/4" hose assembly 18'
6386	680131 1/4" hose assembly 24'
6349	Collett assembly 32mm 1st section 18'
6351	Collett assembly 2nd section of 18'
6385	Collett assembly 1st section of 24' pole
6387	Collett assembly 2nd section of 24'
6401	Collett assembly 3rd section of 24'
6360	2100244 replacement 18' tele-pole
6420	2100245 replacement 24' tele-pole

Giraffe Accessories

Fitted with a 22mm plug for easy attachment to the 22mm connector on the pole outlet, and a 1/4" FPT quick connect for a QC nozzle

Gutter Cleaner



Blast debris from gutters without a ladder. Angled for direct spray in gutters, down spouts.

Part	Product
6739	Gutter kit

Rotating Brush

When additional agitation is required for cleaning high areas.



Part	Product
5005	Brush kit



SprayFlex Accessory

McCauley Sprayflex attachment for hard to reach areas, without a ladder



Part	Product
6738	Sprayflex kit 3000 PSI

The Original



Anti-fatigue Strap & Belt

Reduce the strain of holding a telescopic wand for extended periods of time.

Part	Product
4025	Belt & clamp

McCauley's



- Work more efficiently, with more control
- Increase job safety while cutting waste
- Spray Flex adjusts up to 90 degrees
- 1/4" FPT x 1/4" MPT
- 210°F. Maximum

Part	Product
4598	Spray flex 3000 PSI
4599	Spray flex 5000 PSI



The first and only gutter cleaning applicator on the market designed to use almost any all purpose cleaner.

Synthetic lambs wool applicator pad resists wear and tear

Part	Product
6272	Marxoff Gutter Cleaner
6279	Marxoff synthetic Lambswool refill



Gutter Cleaner

Quick connect to lance to clean gutters or other hard to reach areas. Lance bent to shoot water directly into the gutter with little effort.



Part
6642