



Swivel Hose Reels

- Reel swivels 200°
- Adjustable friction brakes
- Easy push/pull lock pin
- Smooth radius bent arm
- Heavy cold rolled metals
- 1/2" FPT in/out
- 4000 PSI 250°F

Slide-In

Part	Size
5700	K01-2024 100 ft
5718	K01-0206 200 ft

Drop-In

Part	Size
5701	K01-2025 100 ft.
5719	K01-0207 200 ft

Wall Mount

Part	Size
5707	K01-2027 100 ft
5728	K01-0208 200 ft

Flat Surface Mount

Part	Size
5709	K01-2028 100 ft
5729	K01-0209 200 ft

Mount Block

Easy mount adapter mounts to any round or square tubing

Part	Size
5702	K01-2026 100 ft



Universal Hose Reel Swivel

- 8 GPM maximum
- 3000 PSI maximum
- 300°F. maximum

Part	Size
1778	Adams 1/2FPT I/O
1779	Repair kit



JE Adams 90° Swivels

- Swivels under pressure
- 200°F. maximum
- 7 GPM maximum
- 3/8MPT x 3/8FPT

Part	Size	PSI
2295	Stainless Steel	5000
2608	Brass	3000
2294	Repair kit 2295	



Heavy duty swivel for guns, hose reels, booms

- Swivels under pressure
- 5000 PSI maximum
- Ball Bearing design
- 400° maximum

Part	Product
4523	In line 1/4MPT x 1/4FPT
4526	In line 3/8MPT x 3/8FPT
5880	90° 3/8MPT x 3/8FPT
4577	90° 3/8FPT x 3/8FPT
6626	90° 1/2FPT x 3/8FPT Rapid Reel replacement
4575	In line 1/2MPT x 1/2FPT
4578	90° 1/2MPT x 1/2FPT
5881	90° 1/2FPT x 1/2FPT
4579	1/4" Repair kit
4580	3/8 and 1/2 repair kit



90° Swivels

- 250°F. maximum
- 30 RPM maximum
- O-ring seal
- Dual sliding bearing system
- Stainless steel inner part
- Brass, nickel body

Applications: Hose reels, ceiling booms, surface cleaners

5000 PSI maximum

Part	Mos	Product
7000	43.451	WDE 1/4F x 1/4M
7001	43.452	WDE 3/8F x 3/8M
7002	43.453	WDE 1/2F x 1/2M
7003	43.458	WDE 1/2F x 1/2F
7004	43.912	WDE Seal Kit



4000 PSI maximum

6926	43.252	WDB 3/8F x 3/8M
------	--------	-----------------



Applications: Hose reels, ceiling booms, Automatic Car wash Systems

Part	Mos	Product
6928	43.354	WDC 1/2F x 1/2F
6927	43.353	WDC 1/2F x 1/2M
6929	43.904	WDB/WDC kit



In-Line Brass Swivels

Made in the USA

DGV

Live Swivels

Mount the DGV series to any type of high pressure gun, lance or whip line for an easy turning, low maintenance swivel.

- 4000 PSI maximum
- 250°F maximum
- 30 RPM maximum
- Stainless steel, brass nickel body
- Stainless steel inner part
- Single bearing system

Part	Mosmatic	Product
6935	32.552	1/4M x 1/4F
6920	32.564	3/8M x 3/8F
6319	E-3476	3/8M x 1/2F





ST-301

- 5.2 GPM maximum
- 300°F. maximum
- Brass and stainless steel

Part	Size	PSI
6644	3/8MPT x 3/8FPT	5070

ST-340 Hi Flow

Perfect for connecting to trigger guns, booms

- Brass
- Double teflon slide rings
- 42 GPM maximum
- 3625 PSI maximum
- 195°F. maximum

Part	Size
6645	1/2MPT x 1/2FPT



- 10.5 GPM maximum
- 4050 PSI
- 320°F. maximum

Part	Size
2030	PA 1/4M/F
6244	PA 3/8M/F



- 7.8 GPM maximum
- 3000 PSI
- 302°F. maximum

Part	Size
1295	Mecline 3/8" M/F



In-Line Stainless Steel Swivels

- 5000 PSI maximum
- Swivels under pressure
- 200° F. maximum

Part	Size
2235	Adams 1/4 FPT x 1/4 MPT
2238	Adams 3/8 FPT x 3/8 MPT
2236	Adams 1/4" repair kit
2237	Adams 3/8" repair kit



- 10.5 GPM maximum
- 5650 PSI
- 320°F. maximum

6755	PA 1/4MPT x 1/4FPT
6754	PA 3/8MPT x 3/8FPT



Ball Bearing Swivels

- 3500 PSI maximum
- 180°F. maximum
- Swivels under pressure

304 Stainless Steel Swivels

Part	Product
3786	1/4FPT x 1/4MPT
3787	3/8FPT x 3/8MPT
6779	1/2FPT x 1/2MPT
3796	1/4" repair kit
3797	3/8" repair kit
6780	1/2" repair kit



Brass Swivels

212°F. maximum



Part	Product	PSI
3488	1/4MPT x 1/4FPT	2000
3489	1/4MPT x 1/4FPT	3500
3490	3/8MPT x 3/8FPT	2000
3491	3/8MPT x 3/8FPT	3500
3494	90° 3/8MPTx3/8FPT	3500
3495	90° 1/2MPTx1/2FPT	3500
3492	Repair kit for all	

High Speed Swivels

DYCI Series

Triple Bearing System (2 radial ball bearings and 1 thrust ball bearing)

Applications: High RPM, Surface cleaners, Parts cleaners, Tire cleaners



Part	Mos #	Size
6168	55.153	3/8 F x 3/8 M
6022	55.163	3/8 F x G 3/8 M
5903	36.906	Seal kit

DYT Series

Quadruple Bearing System (2 radial ball bearings and 2 thrust ball bearing)

- Carbide Seal
- Complete Stainless
- Live swivel
- 2000 RPM maximum
- 5000 PSI maximum
- 250°F. maximum

Applications: High RPM, High Pressures, thrust and radial force, Surface cleaners, Parts cleaners



Part	Mos #	Size
6496	59.051	1/4" F x 1/4" M
6131	59.153	3/8" F x 3/8" M
6925	59.163	3/8" F x G3/8M
5903	36.906	Carbide seal kit

Triple Bearing System (2 radial ball bearings and 1 thrust ball bearing)

- Carbide Seal
- Brass, nickel plated body
- 4000 PSI maximum
- 2000 RPM maximum
- 250°F maximum

DYG Series with Bulkhead Fitting

Part	Mos #	Size
6879	57.051	1/4 F x 1/4 M
6880	57.153	3/8 F x 3/8 M
6924	57.163	3/8 F x G3/8 M
5903	36.906	Carbide seal kit



DYF Series with Flange

Part	Mos #	Size
6922	58.153	3/8 F x 3/8 M
6923	58.163	3/8 F x G3/8 M
5903	36.906	Carbide seal kit

